PAGE: 1 PRINT DATE: 04/11/98

FAILURE MODES EFFECTS ANALYSIS (FMEA) - NON-CIL HARDWARE NUMBER:M5-6SS-0608A -X

SUBSYSTEM NAME: ISS DOCKING SYSTEM

REVISION: 0

02/27/98

PART NAME	PART NUMBER
VENDOR NAME	VENDOR NUMBER

PART DATA

LRU :AW82D PANEL

VO75-730153

SRU :TOGGLE SWITCH

ME452-0102-7105

SRU :TOGGLE SWITCH ME452-0102-7605

EXTENDED DESCRIPTION OF PART UNDER ANALYSIS:

TOGGLE SWITCH, 1 POLE, 2 POSITION, MOMENTARY ON - EMU 1 AND 2 WATER SUPPLY VALVE CONTROL CIRCUIT

REFERENCE DESIGNATORS:

84V73A139S1

84V73A139S3

QUANTITY OF LIKE ITEMS: 2

(TWO)

FUNCTION:

OPEN OR CLOSE THE EXTRAVEHICULAR MOBILITY UNIT (EMU) WATER SUPPLY VALVES. WATER IS SUPPLIED TO THE EMU'S DURING PRE-BREATHE.

REFERENCE DOCUMENTS:

1) VS70-640109, SCHEMATIC DIAGRAM - AIRLOCK

ENVIRONMENTAL CONTROL SUBSYSTEM

FAILURE MODES EFFECTS ANALYSIS FMEA -- NON-CIL FAILURE MODE

NUMBER: M5-688-0608A-03

REVISION#: 0

02/27/98

SUBSYSTEM NAME: ISS DOCKING SYSTEM.

LRU: AW82D PANEL

ITEM NAME: TOGGLE SWITCH

CRITICALITY OF THIS

FAILURE MODE: 1R3

FAILURE MODE:

FAILS CLOSED IN THE "VALVE CLOSED" POSITION, CONTACT-TO-CONTACT SHORT

MISSION PHASE:

OO ON-QRBIT

VEHICLE/PAYLOAD/KIT EFFECTIVITY:

103 DISCOVERY

104 ATLANTIS 105 ENDEAVOUR

CAUSE:

A) PIECE PART STRUCTURAL FAILURE, B) CONTAMINATION, C) VIBRATION, D) MECHANICAL SHOCK, E) PROCESSING ANOMALY, F) THERMAL STRESS

CRITICALITY 1/1 DURING INTACT ABORT ONLY? NO

CRITICALITY 1R2 DURING INTACT ABORT ONLY (AVIONICS ONLY)? NO

REDUNDANCY SCREEN

A) PASS

B) PASS

C) PASS

PASS/FAIL RATIONALE:

A)

B)

C)

CORRECTING ACTION: NONE

CORRECTING ACTION DESCRIPTION:

DESIGN FAULT TOLERANCE: TOGGLE SWITCH OF WATER SUPPLY VALVE CIRCUIT FOR SECOND EMU SERVICE POINT REMAINS OPERATIONAL. BOTH EMU'S CAN STILL BE SERVICED.

PAGE: 9 PRINT DATE: 04/11/98

FAILURE MODES EFFECTS ANALYSIS (FMEA) - NON-CIL FAILURE MODE NUMBER: M6-688-0608A-03

- FAILURE EFFECTS -

(A) SUBSYSTEM:

LOSS OF CAPABILITY TO OPEN AFFECTED EMU WATER SUPPLY VALVE.

(B) INTERFACING SUBSYSTEM(\$):

FUNCTIONAL DEGRADATION. CANNOT SIMULTANEOUSLY CONNECT AND SERVICE TWO EMU'S TO THE WATER SUPPLY LINES.

(C) MISSION:

FIRST FAILURE - NO EFFECT

(D) CREW, VEHICLE, AND ELEMENT(S):

FIRST FAILURE - NO EFFECT

(E) FUNCTIONAL CRITICALITY EFFECTS:

POSSIBLE LOSS OF CREWIVEHICLE AFTER THREE FAILURES:

- EMU 1 SUPPLY WATER SWITCH FAILS CLOSED IN "VALVE CLOSED" POSITION. LOSS OF CAPABILITY TO SERVICE TWO EMU'S SIMULTANEOUSLY FROM THE WATER SUPPLY CONNECTIONS. ONE OPERATIONAL SUPPLY WATER CONNECTION REMAINS.
- 2) EMU 2 SUPPLY WATER SWITCH FAILS CLOSED IN "VALVE CLOSED" POSITION. LOSS OF NOMINAL WATER SUPPLY TO EMU'S. WORST CASE IF FAILURE OCCURS FOLLOWING AN INITIAL EVA. THEN LOSS OF WATER SUPPLY TO REFILL THE EMU SUBLIMATOR TO PROVIDE COOLING FOR BOTH EMU'S WOULD PRECLUDE SUBSEQUENT EVA CAPABILITIES.
- 3) A FAILURE NECESSITATING AN EVA TO PREVENT A POTENTIAL CATASTROPHIC SITUATION - INABILITY TO PERFORM A CONTINGENCY EVA TO CORRECT A CRIT 1 CONDITION COULD RESULT IN A LOSS OF CREW/VEHICLE.

DESIGN CRITICALITY (PRIOR TO DOWNGRADE, DESCRIBED IN (F)):

(F) RATIONALE FOR CRITICALITY DOWNGRADE:

ALTHOUGH THE CRITICALITY REMAINS UNCHANGED AFTER WORKAROUNDS CONSIDERATION (ALLOWED PER CR \$050107W), THEY ARE PROVIDING ADDITIONAL FAULT TOLERANCE TO THE SYSTEM.

AFTER THE THIRD FAILURE (FAILURE NECESSITATING AN EVA TO PREVENT A POTENTIAL CATASTROPHIC SITUATION) - INABILITY TO PERFORM CONTINGENCY EVA (FOURTH FAILURE) TO CORRECT A CRIT 1 CONDITION COULD RESULT IN LOSS OF CREW AND VEHICLE.

PAGE: 10 PRINT DATE: 04/11/98

FAILURE MODES EFFECTS ANALYSIS (FMEA) -- NON-CIL FAILURE MODE NUMBER: M5-6SS-0608A-03

- TIME FRAME -

TIME FROM FAILURE TO CRITICAL EFFECT: DAYS

TIME FROM FAILURE OCCURRENCE TO DETECTION: MINUTES

TIME FROM DETECTION TO COMPLETED CORRECTING ACTION: MINUTES

IS TIME REQUIRED TO IMPLEMENT CORRECTING ACTION LESS THAN TIME TO EFFECT? YES

RATIONALE FOR TIME TO CORRECTING ACTION VS TIME TO EFFECT: THE WATER SUPPLY VALVE CIRCUIT FOR THE SECOND EMU SERVICE POINT REMAINS OPERATIONAL - BOTH EMU'S CAN STILL BE SERVICED.

HAZARD REPORT NUMBER(\$): NONE

HAZARD(S) DESCRIPTION:

NONE

- APPROVALS -

SS&PAE

DESIGN ENGINEERING

: T. K. KIMURA

: C. J. ARROYO